

LANGFORD

DIRECT



Trailflex is a low cost, environmentally friendly and completely SuDs compliant permeable paving flexible up to 90°.

Fully compliant with Sustainable Urban Drainage System (SuDS), and BREEAM accredited, Trailflex is a low-cost porous paving surface that will not clog and requires virtually no maintenance. Providing fast and efficient drainage of rainwater the unrivalled porosity can drain up to 80,000 litres per square metre per hour replenishing groundwater and allowing surrounding trees and plants to thrive.

The one-part cold poured system consists of recycled car tyres

and stone bound with our specially developed resin creating one of the greenest paving solutions on the market today.

Fast to install, Premium+ Mesh Trailflex can be trafficked in under 24 hours and makes for an extremely robust system suitable for foot traffic in town or country.*

*Subject to ground conditions & weight. Check with technical for advice. For pedestrian use only

ADVANTAGES

Flexible permeable paving - Flexible to 90°, totally porous and clog resistant, forming a low maintenance paving surface

Unrivalled porosity - A highly effective soakaway efficiently managing up to 80,000 litres per square metre per hour

Impervious to tree root intrusion - The adaptable surface removes the risk of root intrusion and subsequent cracking

No Dig Option - Can be laid directly onto existing ground

SuDs compliant - 360 Degree attenuation and BBA approved system

Fast installation and curing - Areas can be trafficked in under 24 hours after completion

3 - TYRES RECYCLED PER METRE²

Trailflex recycles up to 3 tyres for every square metre laid and can help offset your carbon footprint.* Contact us to find out more.

* This specification is based on normal good practice for flexible surfacing and does not absolve the specifier on designing a construction suitable for the expected traffic and ground conditions pertaining to a given site.



20 - YEAR GUARANTEE & 10 - YEAR POROSITY GUARANTEE

Trailflex allows small particles of dirt and grit to agitate through ensuring the surface remains permeable. This allows us to offer a 10 year no clog guarantee.





LANGFORD

- DIRECT -



Trailflex Porous Paving 35-50mm - An innovative surface comprised of resin bound recycled tyres and aggregate. Used as a fully permeable and eco-friendly alternative to



Premium+ Mesh - A heavy-duty ground reinforcement can be laid directly onto the existing ground, creating a

MAINTENANCE

continual porosity.

freeze/thaw process.

Trailflex allows small fines/grit to agitate

through the surface as the area is used.

This produces a hostile environment for

weeds and seedlings and ensures

Allowing expansion and contraction

temperatures such as frost and ice which may otherwise cause damage during the

Trailflex is unaffected by low



Existing ground - Sub-grade

SPECIFICATION ADVICE

Typical groundwork specifications

Footpaths Only – Clean any debris from area. Lay Geo-textile membrane, then overlay with Premium+ Mesh. Trailflex will then be laid onto prepared surface. (Subject to ground conditions & weight. Please check with technical for advice.)

Speed of cure

4 - 16 hours (Weather dependant)

Typical construction

35-50mm Trailflex Porous Paving Premium+ Mesh

Geo-textile Membrane

LANGFORD DIRECT LTD

Piccadilly House, 49 Piccadilly Gardens, Manchester, M1 2AP

0330 900 2288

info@langforddirect.co.uk www.langforddirect.co.uk







